



ALLDRY WALL FIX 4 Waterproof Coating

Alldry Wall Fix 4 is a waterproofing basecoat for vertical walls. It acts as a perfect waterproofing basecoat for all Birla Opus Exterior Emulsions. It is a unique product owing to its high water resistance and ability to withstand high water pressure.

PRODUCT BENEFITS



WATERPROOFING

Safeguards against Positive hydrostatic pressure of upto 5 Bar on wall



MECHANICAL STRENGTH

The acrylic fibres give toughness to the thick film



ADHESION

Strong adherence to the concrete/masonry substrate




WARRANTY

Up to 4-year waterproofing warranty on exterior-walls as a basecoat under Birla Opus Exterior topcoat. The Warranty period will depend on Birla Opus exterior topcoat applied.

PRODUCT DETAILS

ESTIMATED FORCED COVERAGE

3.71-4.18 sq.m/L
(40-45 sq.ft/L)



Recommended usage – To be applied on plastered vertical surface like parapet, sunshades and exterior walls using brush or roller.

AVAILABLE PACKS



COLOURS AVAILABLE



WHITE

DRYING TIME TO TOUCH



between recoats

APPLICATION DETAILS

SURFACE PREPARATION

New masonry surfaces must be allowed to cure completely for 28 days.

Existing Surface should visually inspected for conditions, prepare the surface thoroughly by cleaning, washing, and removing dust, dirt, oil, grease, and loose particles to avoid adverse effects on the adhesion of newly applied products.

REPAIRING

Areas with Structural defects need to be rectified before application.

All should be properly treated. For filling cracks up to 5mm, use Alldry Crack Master Paste. Bigger cracks, damaged or hollow portions, sharp edges, etc. must be cut and repaired with a polymer-modified mortar using Alldry Repair Master.

The surface should be in Surface Saturated Dry (SSD) before application of coating.



ADITYA BIRLA
PAINTS

ALLDRY WALL FIX 4

	STEP	% DILUTION	RECOATING PERIOD	ESTIMATED FORCED COVERAGE
Vertical Surface Application Fresh Painting: 2 coats application with effective coverage of 40-45 sq ft/L Repainting: 1 undiluted coat application with effective coverage 40-45 sq ft /L	Primer Coat	10% with potable water	4-6 hours	Effective coverage 40-45 sq ft /L
	1 st Coat	Without Dilution	4-6 hours	

SAFETY ASPECTS

- Kindly refer to the MSDS, which gives detailed information on safety measures while handling the paint, which is available on request.
- Store the container with the lid tightly closed in an upright position, in a cool, dry place.
- Keep out of reach of children and away from eatables.
- May be harmful if swallowed. In case of ingestion, seek immediate medical attention.
- Wear eye protection during application. In case of contact with eyes or skin, rinse immediately with plenty of water and seek medical advice if irritation persists.
- No added Lead, Mercury or Chromium compounds.
- Left-over paint/drums should not be disposed in soil or drains or water courses.

PRECAUTIONS

- Do not apply when ambient temperature is less than 10°C or above 40°C
- For surfaces having heavy algal infestation, cleaning with bleaching solution is advised.
- Keep the material closed when not in use.
- Do not apply on wet or visibly damp surfaces or when humidity > 80%
- Do not apply if rain is expected within 48 hours after application.

TECHNICAL INFORMATION

Drying Time	4-6 hours
Appearance	Viscous liquid
Color	White
Tensile Strength	Upto 2.5 N/mm ²
% Elongation	Upto 100
Resistance to Positive Hydrostatic pressure	Passes 5 bar
Shelf Life	36 months